

517894

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002870 A1

(51) International Patent Classification⁷: **B66C 1/10**,
1/66, B66F 9/18

(21) International Application Number:
PCT/FI2003/000469

(22) International Filing Date: 12 June 2003 (12.06.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20021249 26 June 2002 (26.06.2002) FI

(71) Applicant (for all designated States except US):
FINNLINES OYJ [FI/FI]; PL 197, FIN-00181 Helsinki
(FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): NISKANEN, Mika
[FI/FI]; Koulumestartie 11 D, FIN-00680 Helsinki (FI).

(74) Agent: FORSSÉN & SALOMAA OY; Eerikinkatu 2,
FIN-00100 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE AND METHOD FOR HANDLING CONTAINERS



(57) **Abstract:** The invention relates to a device in the handling of containers, by means of which device (30) at least two containers (10) are handled. The device (30) comprises a frame (10), to whose guides (11) end pieces (12) have been movably attached, which end pieces (12) comprise attachment members (31, 32) for attaching the device (30) to the corner fittings of the lowermost container(s) (20) of the containers (20) placed on top of one another. The invention also relates to a method in the handling of containers, in which method at least two containers (20) are handled by means of a container transfer device, which container transfer device comprises a gripping member or equivalent. In the method, at least two containers (20) placed on top of one another are handled. In the method for handling containers (20), a device (30) is attached to the gripping member (50) of the container transfer device, which device (30) is placed on the containers (20), placed on top of one another, and attached to corner fittings (21, 22) of the containers (20) such that attachment members (31, 32) situated on end pieces (12) fixed to guides (11) of a frame (10) of the device (30) are arranged to be attached to the apertures in the corner fittings (21, 22) of the container (20).

WO 2004/002870 A1

Device and method for handling containers

5 The invention relates to a device according to the preamble of claim 1.

The invention also relates to a method according to the preamble of claim 10.

10 As known in the art there exist standards relating to the size and structures of containers. ISO standard 668: 1988/1:1993 specifies the location of the corner fitting apertures of the container with respect to one another, and the dimensions of the containers. ISO standard 1161 specifies the shape of the corner fitting apertures of the container, and the permissible mode of handling the container is specified in the standard SFS-ISO 3874.

15 As known in the art, empty containers generally weigh below 5000 kg. The standardized container lengths are 10, 20, 30 and 40 feet. The 40 foot long containers have a height of either 8½ feet or 9½ feet and the 20 foot long containers have a height of 8½ feet. The prior-art container moving devices, for example, straddle carriers, usually comprise length adjustment, so that the
20 handling length can generally be adjusted to be 20, 30 or 40 feet. Applications are also known in which the handling length can be adjusted to be 35 feet. Containers are handled as empty and as full.

25 With respect to the prior art, reference may be made, for example, to *US patents 3,863,970, 5,280,980 and 6,145,903*. In these prior-art arrangements, which mainly relate to the handling of full 20 foot containers, two containers are placed longitudinally one after the other in the handling equipment. Such devices are generally massive because full containers weigh as much as 40 tonnes. In
30 addition, handling is problematic because the structure with its containers

becomes rather long, and therefore they also have not been suitable for the handling of longer 40 foot containers.

5 As known in the art, empty containers are stored in ports such that several containers are placed one upon the other. Containers are handled by means of transfer and transport devices, for example, straddle carriers, the gripping member of which grips the container from above one container at a time, so that the container can be transferred to a desired location.

10 An object of the invention is to create a device and a method for handling of containers in order to handle several containers simultaneously by a container transfer device.

15 One object of the invention is to provide a device for use in connection with a container transfer device, for example, a straddle carrier, and a method in which the auxiliary device is used.

20 With a view to achieving the objects described above as well as those coming out later, the device according to the invention is mainly characterized in what is stated in the characterizing part of claim 1.

The method according to the invention is in turn mainly characterized in what is stated in the characterizing part of claim 10.

25 The invention can be applied in connection with the handling of containers that comply in respect of their height with the standards in force such that the location of the corner fittings is known. One exemplifying embodiment of the invention is suitable for handling containers that comply with the standard in respect of their length, but another exemplifying embodiment of the invention is suitable for use
30 also in connection with containers the length of which does not comply with the standard.

One requirement of the method and the device in accordance with the invention is that the containers placed one upon the other and handled at the same time by the device and in the method shall be of equal length. Height does not impose any
5 limitations.

The device used in connection with the invention is a lifting device which is attached to a length-adjustable gripping member of a container transfer device, for example, a straddle carrier and which enables two or more containers to be lifted
10 and transported.

In accordance with the invention, the device comprises members which are attached to the apertures of the container corner fittings and which attachment members have been placed on the end pieces of the device which have been
15 connected to each other by means of longitudinal frame structures. The frame structure of the device can be fixed or telescopic, so that its length can be adjusted.

In accordance with the invention, the device comprises attachment members placed on the end pieces of the device such that those attachment members which
20 are not needed in lifting containers of a certain height, i.e. which are not in use, have been placed such that they retract inside, for example, by applying spring loading, by means of a gas pump or an electric device, so that they will not impede the gripping of the attachment members in use.

25 In accordance with the invention, the end pieces have been connected to each other such that each end piece engages the corner fittings of the lowermost container(s) and, even though the containers stacked on each other would be misaligned, the attachment members find their way to their positions in the corner
30 fitting apertures. Because of this advantageous additional feature, the arrangement in accordance with the invention takes into account the usual small inaccuracy in

stacking because, in practice, containers are never exactly one upon the other. The device in accordance with the invention centers itself such that it grips both or a plurality of stacked containers. The centering can be carried out by means of an actuator, springs, pumps and equivalent.

5

In accordance with an advantageous feature of the invention, the driver of the container transfer device, for example, a straddle carrier, is supplied with information about pins positioned in place, for example, by means of flaps, signal lights or equivalent signaling means known in themselves.

10

The invention is particularly well suited to the handling of empty containers weighing less than 5000 kg, but full/heavier containers can also be handled by means of it. The invention is particularly well suited to the handling of containers of standard length, in particular 20 and 40 foot containers.

15

In accordance with one advantageous additional feature of the invention, when it is desirable to handle containers of non-standard length, it is possible to use the device of the invention that, in accordance with an advantageous additional feature, has been provided with telescopic or slide beams, whereby the length of

20

the device can be adjusted.

In the following, the invention will be described in greater detail with reference to the figures in the appended drawing, but the invention is not meant by any means to be narrowly limited to the details of them.

25

Figures 1A – 1C schematically show the different stages of the operation of the device in accordance with the invention.

Figure 2 shows a modification of the invention when lifting four 20 foot

30

containers at a time.

Figure 3 is a schematic view of an application of the invention when lifting three containers one upon the other.

Figure 4 is a schematic view of an application of the invention as provided with
5 telescopic or slide beams.

As shown in Figs. 1A – 4, the device in accordance with the invention comprises a frame 10 and end frameworks 12 moving on guides 11 of the frame 10. The end frameworks 12 are provided with attachment members 31, 32, for example, pins.
10 The frame 10 is horizontal and the end pieces, i.e. the end frameworks 12, are substantially vertical. When needed, the end framework is provided with a diagonal support 13 to support the structure. The attachment members 31 and 32 are placed on vertical frame structures 15 and 16 of the end framework 12. In Figs. 1 – 4, the container is designated by the reference numeral 20, top corner
15 fittings of the container 20 are designated by the reference numeral 21 and its bottom corner fittings are designated by the reference numeral 22. The top corner fittings 21 have apertures in the upper surface and in the end surface. The bottom corner fittings 22 have apertures in the lower surface and in the end surface. In addition, the corner fittings 21, 22 of the containers 20 usually also have apertures
20 in the side surfaces. Two containers 20 placed one upon the other are handled in the schematic illustration of the different stages of the operation of the device in accordance with the invention shown in Figs. 1A – 1C.

Fig. 1A shows guide pins 34 for both a 40 foot container, 34₄₀, and a 20 foot
25 container, 34₂₀. The guide pins 34₂₀ for the 20 foot container have been omitted from the other figures for the sake of clarity. The guide pins 34₂₀ for the 20 foot container are, for example, movable, so that they do not impede the handling of the 40 foot container. Fig. 1A also shows a gripping member 50 of a container transfer device for engaging attachment points 33₂₀, 33₄₀ of the device 30 in
30 accordance with the invention depending on the length of the container to be handled. The gripping member 50 has been omitted from the other figures for the

sake of clarity. In the following description, only the reference numeral 34 is used of the guide pins for the sake of clarity.

5 In the situation shown in Fig. 1A, the containers 20 are in a stack on top of each other and the device in accordance with the invention has been moved above the containers 20. In this situation, in accordance with the invention, the gripping member 50 of the container transfer device (not shown), for example, a straddle carrier, has engaged by means of its twist lock pins the attachment points 33₂₀ or 33₄₀ of the device 30 in accordance with the invention. When 20 foot long
10 containers 20 are handled, the attachment points 33₂₀ are engaged, and when 40 foot containers are handled, the attachment points 33₄₀ are engaged.

As shown in Fig. 1A, the lifting device 30 is moved above the containers 20 to be transferred and the guide pins 34 provided on the frame 10 are lowered into the
15 apertures in the upper surface of the top corner fittings 21 of the upper container 20 (FIG. 1B). The guide pins provided 34 on the frame 10 are lowered into the upper apertures of the top corner fittings 21 of the upper container 20, whereby the device is positioned in a correct position with respect to the containers 20. The length of the gripping member of the straddle carrier is adjusted so as to be of
20 correct length and the end frameworks 12 are pressed against the end walls of the containers 20 (FIG. 1C). The attachment members, for example, spindle pins, situated on the end frameworks 12 are inserted in through the end apertures of the top corner fittings 21 of the lower container 20, after which the lifting device 30 can be lifted upwards and both containers 20 can be transported simultaneously.

25 In the exemplifying embodiment shown in Figs. 1A – 1C, two 40 foot long containers placed one on top the other are handled, and the containers 20 are 8½ feet high, so that the lower attachment members 32 of the end frameworks 12 retract inside, while the upper attachment members 31 are positioned in the apertures in the end walls of the top corner fittings of the lower container 20, as
30 shown in Fig. 1C. Detachment of the containers 20 takes place after they have been lowered to the ground such that the length of the gripping members of the

straddle carrier is adjusted to be longer and the lifting device 30 is lifted away from top of the containers 20. The lifting device 30 attached to the container transfer device is moved onto containers 20 which are to be transferred/lifted.

- 5 The length of the gripping member of the container transfer device is shortened from 35 feet to 30 feet, so that the spindle pins 31 on the end pieces 12 are inserted in through the end apertures of the top corner fittings 21 of the lower container 20. If the lower container 20 is not quite exactly aligned with the upper container 20, a spindle beam 17 moves in a lateral direction and guide members
10 37 (FIG. 5) leaning against the side surfaces of the corner fittings 21 align the spindle pins 31 with the apertures.

In Figs. 1A – 1C, the upper container 20 is 8½ feet high, so the lower spindle pin 32 is pressed against the corner post of the lower container 20, yielding as spring-
15 loaded. Similarly, if the upper container 20 is 9½ feet high, the upper "unnecessary" spindle pin yields in a corresponding manner.

If the containers to be lifted are 20 feet long, the pins on the frame at the 20 foot container 20 are lowered into the apertures of the top corner fittings 21. After that,
20 the operation is continued as described above.

As shown in the figures, in accordance with the invention, in the lower part of the end frameworks 12 there are attachment members 31, 32, for example, spindle pins at two different levels, thus enabling the handling of both 8½ foot and 9½
25 foot high containers 20. These attachment members 31, 32 include guides 34 and a mechanism 37 which enables handling of the container 20 although they would not be quite exactly on top of each other.

As shown in the application of Fig. 2, in accordance with the invention it is
30 possible to lift and move, for example, four 20 foot long containers 20 at the same time if the lifting height of the lifting machine, for example, a straddle carrier, is

sufficiently great. In that case, the end piece 12 engages the bottom corner fittings 22 of the lower containers 20.

5 The frame 10 of the device 30 in accordance with the invention is provided with guides and it is a framework that is, for example, about 12 m long and 2.5 m wide, and it incorporates the guide pins 34 needed for the alignment of the invention, as well as the end pieces 12 moving on its guides 11. As shown in Fig. 4, the frame 10 can be alternatively replaced with a telescopic profile, in which case the alignment spindles 34 are situated on the end pieces 12. The end piece 12 is
10 composed of horizontal beams 15 moving on the guides 11 of the frame 10, support beams 13 between them, attachment points 33₂₀, 33₄₀ for the twist lock pins of the container transfer device, vertical beams 16 and spindle beams 17, 18 on which the spindle pins 31, 32 are located.

15 As shown in Fig. 3, the invention is also suitable for use when lifting three containers 20 placed on top of one another. In that case, the end pieces 12 are placed such that the attachment members, i.e. the spindle pins 32, of the end pieces 12 are placed in the bottom corner fittings 22 of the lowermost container 20.

20 Above, the invention has been described with reference to some of its advantageous exemplifying embodiments only, but the invention is not meant by any means to be narrowly limited to the details of them.

Claims

1. A device in the handling of containers, by means of which device (30) at least two containers (10) are handled, which device (30) comprises a frame (10), to whose guides (11) end pieces (12) have been movably attached, which end pieces (12) comprise attachment members (31, 32) for attaching the device (30) to the corner fittings of the lowermost container(s) (20) of the containers (20) placed on top of one another, **characterized** in that guide pins (34) used for aligning the device (30) have been fixed to the frame (10) or to the end pieces (12) moving on the guides of the frame (10), which guide pins have been arranged to be placed into the apertures in the upper surface of the top corner fittings of the uppermost container(s) of the containers (20) placed on top of one another, and that the device has been arranged to be attached to a gripping member of a container transfer device.
2. A device as claimed in claim 1, **characterized** in that the device (30) comprises attachment members (31, 32) which are attached to the apertures of the corner fittings of the container (20) and which attachment members (31, 32) have been placed on the end pieces of the device (30) which have been connected to each other with longitudinal frame structures (10, 11).
3. A device as claimed in claim 1 or 2, **characterized** in that the frame (10) of the device (30) is a framework provided with guides (11).
4. A device as claimed in any one of claims 1 to 3, **characterized** in that the end pieces (12) of the device (30) comprise horizontal beams (15) movable on the guides (11) of the frame (10), support beams (13) and attachment points (33₂₀, 33₄₀) for twist lock pins of a container transfer device, and vertical beams (16) and beams (17, 18) to which the attachment members (31, 32) have been fixed.

5. A device as claimed in any one of claims 1 to 4, **characterized** in that the attachment members (31, 32) are flexible such that the attachment members which are not in use retract inside.

5 6. A device as claimed in any one of claims 1 to 5, **characterized** in that the guides (11) of the frame (10) are telescopic frames, so that the length of the frame can be adjusted (FIG. 4).

7. A device as claimed in any one of claims 1 to 6, **characterized** in that the
10 frame (10) of the device is fixed.

8. A device as claimed in any one of claims 1 to 7, **characterized** in that the device (30) is a lifting device attached to a length-adjustable gripping member of a container transfer device.

15

9. A device as claimed in any one of claims 1 to 8, **characterized** in that the device (10) comprises guide pins (34) which have been arranged to be positioned in the apertures of the upper surface of the top corner fittings of the uppermost container, and a guide member (37) disposed in connection with the end piece to
20 centre the device in place.

10. A method in the handling of containers, in which method at least two containers (20) are handled by means of a container transfer device, which container transfer device comprises a gripping member or equivalent, in which
25 method at least two containers (20) placed on top of one another are handled and in which method for handling containers (20) a device (30) is used which is placed on the containers (20), placed on top of one another, and attached to corner fittings (21, 22) of the containers (20) such that attachment members (31, 32) situated on end pieces (12) fixed to guides (11) of a frame (10) of the device (30)
30 are arranged to be attached to the apertures in the corner fittings (21, 22) of the container (20), **characterized** in that, in the method, the device (30) is aligned in

place by means of guide pins (34) placed on the frame (10) or on the end pieces (12), which guide pins (34) are placed in the apertures of the upper surface of the top corner fittings (21) of the uppermost container (20), and that the device used in the method is attached to the gripping member of the container transfer device.

5

11. A method as claimed in claim 10, characterized in that, in the method, the device is further aligned in place by means of guide members (37) fixed to the end pieces (12).




FIG. 1A

2/7




FIG. 1B




FIG. 1C

4/7




FIG. 2

5/7




FIG. 3

6/7




FIG. 4

7/7




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 03/00469

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B66C 1/10, B66C 1/66, B66F 9/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B66C, B66F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6138846 A (J.A. BAUMANN), 31 October 2000 (31.10.00), column 3, line 47 - line 65; column 4, line 1 - line 9, figures 2-5 --	1-4,6-8,10
X	DE 3621648 A1 (ERICH BEHN MASCHINEN- UND FEINSTAHLBAU GMBH), 14 January 1988 (14.01.88), column 6, line 1 - line 44, figures 1,8 --	1,2,6-10
X	WO 9806656 A1 (ALL SET MARINE, INC.), 19 February 1998 (19.02.98), page 6, line 28 - line 36, figure 2 --	1,2,6,10
A		3-5,11

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 Sept 2003

Date of mailing of the international search report
15 -09- 2003Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Björn Lindkvist / MRO
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 03/00469

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5718550 A (J.J. LANIGAN, SR. ET AL), 17 February 1998 (17.02.98), figures 1,6, abstract --	1-11
A	GB 2147266 A (MI-JACK PRODUCTS INC.), 9 May 1985 (09.05.85), figure 1, abstract -- -----	1-11

INTERNATIONAL SEARCH REPORT
Information on patent family members

26/07/03

International application No.

PCT/FI 03/00469

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	6138846	A	31/10/00	NONE	
DE	3621648	A1	14/01/88	NONE	
WO	9806656	A1	19/02/98	AU 4067597 A	06/03/98
US	5718550	A	17/02/98	US 5415517 A	16/05/95
				US 5511927 A	30/04/96
GB	2147266	A	09/05/85	AU 555608 B	02/10/86
				AU 1989483 A	18/04/85
				DE 3336458 A,C	25/04/85
				FR 2553079 A,B	12/04/85
				GB 8326013 D	00/00/00
				NL 8303622 A	17/05/85